

# Custom CE Marked Transformers

## SINGLE PHASE



### GLOBAL CONFORMITY

Primary = Custom  
 Secondary = Custom  
 Frequency = 50/60 Hz  
 Temperature Rise = 115°C  
 Conductors = Copper Windings  
 Construction = Finger Safe Terminals  
 Noise Reduction = Electrostatically Shielded



Primary	Custom
Secondary	Custom

### Selected Information

### Terminal Options

VA Size	Catalog Number	Voltage Code	Enclosure Code	Finger-Safe SCREW Terminals	Finger-Safe SPRING Terminals
250	PCE-1-250- _ _ _ - _	Please Call	See Below	Standard	Available
500	PCE-1-500- _ _ _ - _	Please Call	See Below	Standard	Available
750	PCE-1-750- _ _ _ - _	Please Call	See Below	Standard	Available
1000	PCE-1-1K- _ _ _ - _	Please Call	See Below	Standard	Available
1500	PCE-1-1.5K- _ _ _ - _	Please Call	See Below	Standard	Available
2000	PCE-1-2K- _ _ _ - _	Please Call	See Below	Standard	Available
2500	PCE-1-2.5K- _ _ _ - _	Please Call	See Below	Standard	Available
3000	PCE-1-3K- _ _ _ - _	Please Call	See Below	Standard	Available
5000	PCE-1-5K- _ _ _ - _	Please Call	See Below	Standard	Available
7500	PCE-1-7.5K- _ _ _ - _	Please Call	See Below	Standard	Available
10000	PCE-1-10K- _ _ _ - _	Please Call	See Below	Standard	Available
15000	PCE-1-15K- _ _ _ - _	Please Call	See Below	Standard	Available



**C** = Core & Coil ( OPEN )



**P** = Potted ( NEMA-3R )

Transformers with any other KVA ratings and/or voltage combinations are available upon request.