

# Custom Encapsulated Transformers

## SINGLE PHASE



### ISOLATION TRANSFORMER

Primary = Custom

Secondary = Custom

Frequency = 60 Hz ( 50 Hz Available )

Temperature Rise = 115°C ( 55°C Available )

Construction = NEMA-3R ( NEMA-12 Available )



Primary	Custom	Approx. Dimensions ( in Inches )			Enclosure Style	Weight ( in lbs. )
Secondary	Custom	Height	Width	Depth		
KVA Size	Catalog Number					
1.0	EF - - - L1	11.25	5.25	6.50	1	45
1.5	EF - - - L1.5	12.25	6.88	6.25	1	55
2.0	EF - - - L2	12.25	6.88	6.25	1	65
3.0	EF - - - L3	14.25	8.12	7.12	1	80
4.0	EF - - - L4	15.25	12.38	8.63	2	95
5.0	EF - - - L5	15.25	12.38	8.63	2	110
6.0	EF - - - L6	15.25	12.38	8.63	2	115
7.5	EF - - - L7.5	15.25	12.38	8.63	2	125
10.0	EF - - - L10	15.25	12.38	8.63	2	150
15.0	EF - - - L15	15.00	15.50	10.50	2	225
25.0	EF - - - L25	25.12	17.63	12.50	2	345

Note: For Transformers with **CE Certification**, please consult Factory



Enclosure Style # 1



Enclosure Style # 2

Transformers with any other KVA ratings and/or voltage combinations are available upon request.