

Custom CE Marked Transformers

THREE PHASE



GLOBAL CONFORMITY

Primary = Custom
 Secondary = Custom
 Frequency = 50/60 Hz
 Temperature Rise = 115°C
 Conductors = Copper Windings
 Construction = Finger Safe Terminals
 Noise Reduction = Electrostatically Shielded



Primary	Custom
Secondary	Custom

Selected Information

Terminal Options

KVA Size	Catalog Number	Voltage Code	Enclosure Code	Finger-Safe SCREW Terminals	Finger-Safe SPRING Terminals
1.0	PCE-3-1K- ___ - _	Please Call	See Below	Standard	Available
1.5	PCE-3-1.5K- ___ - _	Please Call	See Below	Standard	Available
2.0	PCE-3-2K- ___ - _	Please Call	See Below	Standard	Available
2.5	PCE-3-2.5K- ___ - _	Please Call	See Below	Standard	Available
3.0	PCE-3-3K- ___ - _	Please Call	See Below	Standard	Available
5.0	PCE-3-5K- ___ - _	Please Call	See Below	Standard	Available
7.5	PCE-3-7.5K- ___ - _	Please Call	See Below	Standard	Available
10.0	PCE-3-10K- ___ - _	Please Call	See Below	Standard	Available
15.0	PCE-3-15K- ___ - _	Please Call	See Below	Standard	Available
25.0	PCE-3-25K- ___ - _	Please Call	See Below	Standard	Available
30.0	PCE-3-30K- ___ - _	Please Call	See Below	Standard	Available
45.0	PCE-3-45K- ___ - _	Please Call	See Below	Standard	Available



C = Core & Coil (OPEN)



E = Enclosure (NEMA-1)



P = Potted (NEMA-3R)