

Custom Encapsulated Transformers

THREE PHASE



ISOLATION TRANSFORMER

Primary = Custom
Secondary = Custom
Frequency = 60 Hz (50 Hz Available)
Temperature Rise = 115°C
Construction = NEMA-3R (NEMA-12 Available)



Primary	Custom	Approx. Dimensions (in Inches)			Weight (in lbs.)		
Secondary	Custom	KVA Size	Catalog Number	Height	Width	Depth	Weight
		5	3EF - - - L5-FM	15.50	12.38	8.88	155
		10	3EF - - - L10-FM	17.00	19.25	9.00	220
		15	3EF - - - L15-FM	17.00	19.25	9.00	245
		20	3EF - - - L20-FM	25.50	17.63	12.50	330
		25	3EF - - - L25-FM	25.50	17.63	12.50	460
		30	3EF - - - L30-FM	25.50	17.63	12.50	525
		40	3EF - - - L40-FM	25.50	17.63	12.50	575
		45	3EF - - - L45-FM	24.00	27.00	12.00	625
		55	3EF - - - L55-FM	24.00	27.00	12.00	685
		65	3EF - - - L65-FM	24.00	27.00	12.00	725
		75	3EF - - - L75-FM	24.00	27.00	12.00	775

Note: For Transformers with **CE Certification**, please consult Factory



Transformers with any other KVA ratings and/or voltage combinations are available upon request.