

Custom Encapsulated Transformers

THREE PHASE

ISOLATION TRANSFORMER

Primary = Custom

Secondary = Custom

Frequency = 60 Hz (50 Hz Available)

Temperature Rise = 115°C (55°C Available)

Construction = NEMA-3R (NEMA-12 Available)



Primary	Custom	Approx. Dimensions (in Inches)			Enclosure Style	Weight (in lbs.)
Secondary	Custom	Height	Width	Depth		
KVA Size	Catalog Number					
1.0	3EF - - - L1	14.25	8.12	7.12	1	65
1.5	3EF - - - L1.5	14.25	8.12	7.12	1	75
2.0	3EF - - - L2	15.25	12.38	8.63	2	75
3.0	3EF - - - L3	15.25	12.38	8.63	2	125
4.0	3EF - - - L4	15.25	12.38	8.63	2	135
5.0	3EF - - - L5	15.25	12.38	8.63	2	155
6.0	3EF - - - L6	15.25	12.38	8.63	2	165
7.5	3EF - - - L7.5	16.00	19.25	8.75	2	185
10.0	3EF - - - L10	16.00	19.25	8.75	2	220
15.0	3EF - - - L15	25.12	17.63	12.50	2	245
25.0	3EF - - - L25	25.12	17.63	12.50	2	460
45.0	3EF - - - L45	24.00	27.00	12.00	2	625
75.0	3EF - - - L75	24.00	27.00	12.00	2	775

Note: For Transformers with **CE Certification**, please consult Factory



Enclosure Style # 1



Enclosure Style # 2

Transformers with any other KVA ratings and/or voltage combinations are available upon request.