

Transformers for EXPORTED Machinery

THREE PHASE



VOLTAGE-MATCHING

(2) 2½% FCAN & (2) 2½% FCBN Taps

150°C Temperature Rise

220°C Insulation System

Ventilated NEMA-2 Construction

Indoor Installations (or Add W/S for Outdoor)

	60 Hertz	50 Hertz		
Building Voltage	220 Delta	380 Delta	400 Delta	415 Delta
Machinery Voltage	240Y/139	240Y/139	240Y/139	240Y/139

KVA Size	Catalog Number			
15	3PTN529-15K-Y	3PTN718-15K-Y	3PTN583-15K	3PTN234-15K-Y
30	3PTN529-30K-Y	3PTN718-30K-Y	3PTN583-30K	3PTN234-30K-Y
45	3PTN529-45K-Y	3PTN718-45K-Y	3PTN583-45K	3PTN234-45K-Y
75	3PTN529-75K-Y	3PTN718-75K-Y	3PTN583-75K	3PTN234-75K-Y
112	3PTN529-112K-Y	3PTN718-112K-Y	3PTN583-112K	3PTN234-112K-Y
150	3PTN529-150K-Y	3PTN718-150K-Y	3PTN583-150K	3PTN234-150K-Y
225	3PTN529-225K-Y	3PTN718-225K-Y	3PTN583-225K	3PTN234-225K-Y
300	3PTN529-300K-Y	3PTN718-300K-Y	3PTN583-300K	3PTN234-300K-Y
500	3PTN529-500K-Y	3PTN718-500K-Y	3PTN583-500K	3PTN234-500K-Y



Transformers with any other KVA ratings and/or voltage combinations are available upon request.



www.powertran.com

POWERTRAN
TRANSFORMERS

Phone 248-399-4300 Fax 248-399-1018