

Transformers for EXPORTED Machinery

THREE PHASE



VOLTAGE-MATCHING

(2) 2½% FCAN & (2) 2½% FCBN Taps

150°C Temperature Rise

220°C Insulation System

Ventilated NEMA-2 Construction

Indoor Installations (or Add W/S for Outdoor)

	60 Hertz	50 Hertz		
Building Voltage	220 Delta	380 Delta	400 Delta	415 Delta
Machinery Voltage	480Y/277	480Y/277	480Y/277	480Y/277

KVA Size	Catalog Number			
15	3PTN770-15K	3PTN533-15K	3PTN774-15K	3PTN736-15K
30	3PTN770-30K	3PTN533-30K	3PTN774-30K	3PTN736-30K
45	3PTN770-45K	3PTN533-45K	3PTN774-45K	3PTN736-45K
75	3PTN770-75K	3PTN533-75K	3PTN774-75K	3PTN736-75K
112	3PTN770-112K	3PTN533-112K	3PTN774-112K	3PTN736-112K
150	3PTN770-150K	3PTN533-150K	3PTN774-150K	3PTN736-150K
225	3PTN770-225K	3PTN533-225K	3PTN774-225K	3PTN736-225K
300	3PTN770-300K	3PTN533-300K	3PTN774-300K	3PTN736-300K
500	3PTN770-500K	3PTN533-500K	3PTN774-500K	3PTN736-500K



Transformers with any other KVA ratings and/or voltage combinations are available upon request.



www.powertran.com

POWERTRAN
TRANSFORMERS

Phone 248-399-4300 Fax 248-399-1018