



1. ALL UNITS ARE cUL LISTED & DESIGNED ACCORDANCE WITH INDUSTRY STANDARDS.
2. TRANSFORMERS ARE DRY-TYPE, CLASS AA, ENCAPSULATED NEMA 12 ENCLOSED FOR INDOOR / DUSTPROOF USE.
3. TRANSFORMERS ARE WALL / MACHINE MOUNTABLE VIA THE ATTACHED BRACKETS.
4. TRANSFORMERS ARE CONSTRUCTED BASED UPON A 40°C AMBIENT ENVIRONMENT.
5. MAINTAIN 1" CLEARANCE FROM ALL LIVE PARTS.
6. PAINT COLOR IS RAL# 7042.



SIDE VIEW

TERMINAL VIEW

APPROXIMATE DIMENSIONS ( INCHES )

| KVA | A     | B    | C    | D     | E    | F    | HARDWARE | MTG SLOTS       | ENCLOSURE | lbs. | WEATHER SHIELD | TERMINAL TYPE |
|-----|-------|------|------|-------|------|------|----------|-----------------|-----------|------|----------------|---------------|
| 2.0 | 12.25 | 8.63 | 6.25 | 11.00 | 5.75 | ---- | 1/4-20   | 0.375" x 0.625" | N212-EX   | 50   | N/A            | LEADs         |

\* ELECTROSTATIC SHIELD GROUNDED TO TRANSFORMER CASE AT FACTORY ( IF APPLICABLE )

|                                              |
|----------------------------------------------|
| DRAWINGS                                     |
| <input checked="" type="checkbox"/> APPROVAL |
| <input type="checkbox"/> RECORD              |
| <input type="checkbox"/> OTHER               |

|                                                                                    |                                                                              |                |                                                                        |
|------------------------------------------------------------------------------------|------------------------------------------------------------------------------|----------------|------------------------------------------------------------------------|
| PRIMARY VOLTAGE                                                                    | 240 x 480                                                                    | CUST. XXXXXXXX |                                                                        |
| SECONDARY VOLTAGE                                                                  | 120                                                                          | JOB            |                                                                        |
| TEMPERATURE RISE IN °C                                                             | 115                                                                          | CATALOG        |                                                                        |
| WINDINGS & TERMINALS                                                               | <input type="checkbox"/> ALUMINUM <input checked="" type="checkbox"/> COPPER | NOTE XXXXXXXX  |                                                                        |
| FREQUENCY IN HERTZ                                                                 | 60                                                                           | BY             | ENG. LOG. TITLE 1-PHASE, 600 VOLT CLASS ISOLATION DRY TYPE TRANSFORMER |
| PRIMARY TAPS                                                                       | NONE                                                                         | DATE           |                                                                        |
|  |                                                                              | REV            | MFG. LOG. DWG. NO.                                                     |
|                                                                                    |                                                                              | DATE:          | DWG. FILE NF480L2000                                                   |